

Dr. Nguyen Thi Minh Ngoc
Deutsche Gesellschaft für Internationale Zusammenarbeit GmbH (GIZ)
E-mail: ngoc.nguyen1@giz.de; Tel: +84389663366





On behalf of:




of the Federal Republic of Germany

# ...investment gap and annual losses in Vietnam

Vietnam invests in infrastructure: 400,000 billion VND or USD 20 billion per year or around 9% of GDP.

...meets only 30 % of the investment needs of ministries and localities (MoF Report 2018).

Between 1998 and 2013 average annual losses of 1.5 % of GDP due to extreme weather events in Vietnam (Vietnam University of Economics 2013; World Bank Report 2013)



gíz



Have this infrastructure considered impacts of climate factors yet or not?

Bank erosion on 21/5/2018 in Can Tho, leading to completely collapse of 7 houses and urgent excavation of tens of other houses


"We have reached a pivotal moment. If we do not change course in the next two years, we risk runaway climate change. Climate change is moving faster than we are — and its speed has provoked a sonic boom SOS across our world. [...] The real danger is not the threat to one's economy that comes from acting. It is, instead, the risk to one's economy by failing to act.

Governments need to be courageous and smart. That means [...] stopping investments in unsustainable infrastructure that lock in bad practices for decades to come."

UN Secretary General Guterres at UN General Assembly September 2018

# Making infrastructure investments climate proof

Climate risk assessment as a means of National Adaptation Plan and Policy (NAP) implementation



Page 5 | CSI Project Presentation

### Infrastructure Case - Vietnam

Cai Lon – Cai Be Sluice Gate System

#### Key facts

- Mekong Delta an important region for rice cultivation, fishery & aquaculture
- > Responsible for:
  - > 90% of Vietnam's rice exports
  - > 70% of aquaculture production
- Sluice gates needed to regulate water supply & for the separation of fresh and saltwater

#### Past climatic impacts in the Mekong Delta


- ➤ Heavy rain and extreme floods affect the region
- Damages of USD 71 million/year caused by storms and floods
- ➤ An extreme drought in 2016 caused massive crop failure, also through saltwater intrusion







- In this study, current and future climate risks have been assessed for the Cai Lon Cai Be sluice gates project, which was classified into Group A of new construction works in Vietnam with a total state investment of 3,300 billion VND.
- The project was first proposed in 2006, and recently approved for investment by the Prime Minister and managed by the Hydraulic Project Investment and Construction Management Board No. 10 (PMU 10) under MARD
- The design life of the planned infrastructure is 100 years.







## Infrastructure Case - Vietnam Cai Lon - Cai Be Sluice Gate System

## **Summary of the Climate Information probability scores**

Parameters	Threshold	Unit	Historical probability score	Future probability score
		Climate		
High temperature	≥ 35°C	Days/year	6	7
Heat wave	≥ 8 or more consecutive days with the maximum temperature ≥ 35°C	Events/year	3	4
Heavy rain	≥ 100mm in a day	Days/year	4	5
Heavy 5-day total rainfall	≥250mm	Events/year	4	4
Tropical storms/depression	From level 8 (equivalent to the windy speed of 62 - 74km/h) or more	Events/year	3	4
Drought	K ≥ 4 in dry season	Drought events/30 years	5	6
High wind	≥ 20m/s	Days/year	4	4
Tornado	Fujita wind scale  Based on the statistical data of the  damages	Events/year	1	2
Thunderstorm/ Lightning	Based on the statistical data of the damages	Events/year	5	5
	ŀ	lydrology		
Water level	0.9 m (design probability 5%)	Exceeding value/year	7	7
Salinity	3g/l	Exceeding value/year	7	7
	Cumi	llative effects		
Salinity intrusion + high temperature	Salinity = 3g/l and high temperature ≥ 35ºC	Events/year	4	5
High water level + heavy rain	Water level ≥ 0.9 m and heavy rain ≥ 100mm/day	Events/year	2	4

# Infrastructure Case - Vietnam Cai Lon - Cai Be Sluice Gate System

#### **Climate Risk assessment matrix for future conditions**

Time Period	Clin	nate	and	Oth	er V	ariab	les a	nd E	vent			- 01				2000				213			75	Sau.			-/2				13/			- 0	v.								Г							
2080 - 2099 Infrastructure Components	High		nper 35o0	ature	•	Heat Wave (8 consecutive days >=35oC				Heavy Rain / > 100mm/day			5-day Total Ra >=250mm				Tropical Storm/Depression			n Drought				High Wind >=20 m/s				Tornado			Thunderstorm/ Lightning				,	Water Level				Water Salinit			6	Salinity intrusion combined with high temperature				igh water level combined with heavy rain		
			A			В					-	7	12	D	27	T	77	E		L	4	F			0		$\exists$		Н			1	1				K				L			i e	L			L	-	$\exists$
2-statististicountum	Y/N	P	- 5	A	1/3	P	5	R	Y/N	P	5	R	Y/N	P.	5 8	¥/1	N S	- 1	R	7/9	u P	5	R	Y/N	P	5	-	Y/N	Р	5 1	L 9/8	P	5	8	Y/M	-	5	R	Y/N	,	s	Ř	4/1	P	3	R	Y/N	P	5	A.
Personal	٧	7	2	21	v	4	6	24	v	5	4	20	v	4	3 1	2 V		1 7	7 28	v	6	3	18	γ	4	4	16	Y	2	7 1	4 V	5	7	35									۰	+		-				-
Transportation (Supplies Delivery)	-	-	-	4.1	H	+	Ť	24	v	5	_	10	v	_	1 4	v	_	1 5	_		- U	-	10	-	-	-	10		_	7 1		1	ť	30			+	-			+		٠			+	Н	-		н
2-Statee Gate Structure			_	_	-	_						-			100							100									-		_		_								۰			-				н
Pile foundation					۰											٠				۰																							۰							-
Waterproof pile foundation			Н		+	_	-				$\neg$	_				+	+			+						$\neg$			_		+		-		-			-			_		۰	+		-		_		
Piterfooting			1	+	۰	+	_				_	-		_	+	۰	+	+	_	۰	+			Н		_	_	_	_	_	+		_		Н				Н		1		۰	+	Н		Н	_		н
Bottom beam			Н	+	t	_						$\neg$				+	-			+			=						_		+				-			-			1		۰	+		-				_
Pila			$\vdash$	+	V	4	3	12																												7	2	14	γ	7	2	14	v	5	4	20	Y	4	2	8
Gate tower/ Gate hange					Ý	-	-									_	1					r	_	L		L		П	:4								۲			Ė	۲	۰	۰	Ť	Ť			Ì		
Cast-in-situ concrete composition					Ÿ	4									1	S	K				۲		n		1	1	1	П	П	V		K							Υ	7	2	14	Υ	5	3	15		_		
J-Ship Lock	т		т	т	т				т					•	••	_		•			•	•	_					•	•	·J	-					_	т	$\overline{}$					т				П	$\neg$	$\neg$	П
Lock drambe					Υ	4	2	8																												7	4	28	Υ	7	2	14	Υ	5	4	20	Υ	4	5 7	20
Lock head		П	т	-	γ	4	2	8	т										•	9		1/		ľ	п	٠.										7	4	28	Υ	7	2	14	γ	5	4	20	γ	4	5 7	20
Filling and discharge culvert:		-	$\vdash$	$^{+}$	γ	4	2	8	т										•	J	C	V	C	7	Ц	Ly	•												γ	7	2	14	γ	5	3	15				
Leadingjetty			т		Υ	4	2	8																															Υ	7	2	14	γ	5	3	15	П	$\neg$	$\neg$	
4-Gates (large and small)	$\vdash$		т	-	1				т			П				Т	Т	Т	$\top$	Т							$\neg$				Т				Г	Т	${}^{-}$						Т					$\neg$	$\neg$	П
Hydrau lic Cylin de					1							_				+				+											_								Υ	7	3	21	Υ	5	4	20				
Gates (large and small			т	т	т	_	т	_	т		$\neg$	┪	_	_	_	Y	4	1 6	5 24		-			Υ	4	5	20	Y	2	4	3	_	-		Υ	7	4	28	Υ	7		21	Υ			20	Υ	4	4	16
Water tight gasket	Υ	7	3	21	γ	4	6	24			$\neg$	_	$\neg$		$\top$	1				т	$\top$							$\neg$	$\neg$		$\top$	-	-	-					Υ	7	2	14	γ	5	4	20	П			
5-Brhige			т		Т	-			т		$\neg$	_	$\neg$	$\neg$	-	+	+	+	-	+	-			П		$\neg$	_	$\neg$	$\neg$	$\overline{}$	-	-	-	-	т	-	-	-					т	-	-	-	П	$\neg$	$\neg$	П
Bridge Surface					Υ	4	4	16	Υ	5	2	10				+				+								Υ	2	2 /	1												т							П
Hand Rai			$\vdash$	T								┪		$\neg$		T	$\top$	T	$\top$	T	$\top$									2 4	4				Т		$\vdash$				$\vdash$		T	$\top$	Т			$\neg$	$\neg$	
Lighting System			$\vdash$	$^{+}$	t		T	-	-		$\neg$	┪	$\neg$	_	$\top$	+	$^{+}$	$^{+}$	$\top$	+	-										$\top$	-	-		Н		$\vdash$		Н	$\vdash$	т	т	t	+	-	-	Н	$\neg$	_	
Trieffic Sign Post			т	${}^{-}$	т	-		-	т		$\neg$	┪	$\neg$		$\top$	+	T	T	$\top$	т	$\top$						╗	$\neg$	$\neg$	$\neg$	$\top$				т				П		т	т	т	-	т	-	П	$\neg$	$\neg$	П
(upstream and downstream of stylice gates)	Г	Г	Г	Т	Т	Т	Т	Т	Г			╗	$\neg$	T	T	Т	Т	Т	T	Т	Т	Т				$\neg$		$\neg$	$\neg$	$\top$	Т	Т	Т		Г		Т	П	Г		Т	Т	Т	Т	П	П	П	$\neg$	$\top$	٦
Retaining walls					Υ	4	2	8				┪				T				T											$\top$				Т				Υ	7	2	14	Υ	5	3	15				П
Gabion			Г	Т	Т	Т						7	$\neg$		Т	Т	Т	Т	Т	Т	Т						7		$\neg$		Т	Т					П						T	Т			П	$\neg$	$\neg$	$\neg$
Connected embankments					Υ	4	2	8								Ι	$\mathbf{I}$	$\perp$		Υ	- 6	4	24																Υ	7	2	14	Υ	5	3	15				
Rip-rap embankments section					Υ	4	2	8							I	Ι	Ι	Ι		Γ											$\mathbf{I}$								Υ	7	2	14	Υ	5	3	15				
Riverboni																	Τ	Τ																																
Stilling basin																	$\mathbf{I}$	$\mathbf{I}$												$\perp$																				
7-Operation house					Υ				Υ	5		10				Y	_		12	2				Υ	4	2	8			6 1		÷		5																
8-Park					٧	4	3	12	Υ	5	2	10				Υ	4	7	7 28	Y	6	4	24	Υ	4	4	16	Υ	2	7 1	4 Y	5	7	35																
5-Electric Power					L										$\perp$	$\mathbf{I}$	Ι	Ι		$\mathbf{L}$										$\perp$	$\perp$																			
Transmission Lines					Г				Υ	5		10				Υ			-	)				Υ	4	4	16	Υ		7 1	_	5	7	35																
Power Supply									Υ	5	2	10				Y	4	3	12	2								-	2	3 6	_	5	7	35																
Standby Generators																												γ	2	3 (	5 Y	5	7	35																
10-Control and operation system					Г										I	Γ	Ι	Ι												$\perp$																				
Control Systems																Υ			7 28	3										I	Υ	5	7	35																
Operation systems									Υ	5				4	1 4			5	20	)											γ	5	7	35																
11-Monitoring systems									Υ	5	2	10	Υ	4	1 4	Y	4	7	28	3								Υ	2	7 1	4 Y	5	7	35																
12-Fire actinguishing systems																	Ι	Ι																																
13-Communication system			Г		Г		Г		Υ	5	2	10	Υ	4	1 4	Y	4	7	28	3				Y	4	4	16	Υ	2	7 1	4 Y	5	7	35									Г						Т	



#### Climate risk based Recommendations

Order	Infrastructure components under risk	Proposed measures for climate proofing the infrastructure
1	Pillars, ship locks, etc.	To refer to the materials that have been applied for reducing concrete corrosion in Vietnam; for example, using sulphate resistant cement, anti-corrosion additive mixture, or high grade concrete (M50);
2	Hydraulic cylinders, gates, etc.	To study on mechanisms and causes of metal corrosion in the MKD to have the suitable prevention measure such as using a stainless steel as applied to bridges;
3	Pillars, ship locks, hydraulic cylinders, gates, etc.	To consider the use of the high-quality paintings for concrete and metal to prevent corrosion, such as epoxy painting method as recommended by Vietnam Academy for Water Resources and US Army Corps of Engineers (USACE).
4	Operation systems (Group C)	To consider underground wiring designs to ensure safety under thunderstorms/lightning, tornado or in the rainy season, and no splices/cable junctions at risk (i.e. wet) areas;
5	The whole infrastructure	To design lightning protection systems for the whole infrastructure as applied for Rach Chanh sluice gate in Long An Province;
6	Monitoring system	To select SCADA system (sensor) with high tolerance, as experienced in the sluices gate in Tra Vinh Province;
7	Operation and maintenance staff	To have trainings for staff about the climate/hydrological risks on the infrastructure, and how to cope with the extreme events with the low probability scores (e.g., tropical storms and tornado);
8	Operation and maintenance staff	To use protective equipment and clothing as working outdoors under the high temperature, heavy rain, tropical storms, high wind, tornado or thunderstorms/lightning;
9	Operation and maintenance staff	To use the automatic operation mode or choose the time of proper maintenance in the condition of heat wave, for example, in the afternoon when the temperature is reduced.



# FROM RECOMMENDATION TO ADJUSTMENT

(Adjustment of the Cai Lon – Cai Be Sluice Gate Project during Technical Design and Blueprints)



## Success Factors and Results so far

Pilot application, testing, learning, experience sharing of a new climate risk assessment protocol for infrastructure;

Network Governance: Climate **Service Value** Chain

Established new cooperation between NHMA, MARD (Engineers); Multipliers for new approaches and tools

User-provider exchange on

needed climate information;

Key competences: **Pilot** application of new tools

Application of international tools to elaborate extreme weather projections Institutionalization: Up-scaling, regulatory framework and global exchange

Integration into Plans: Decree 37 Planning of the Planning Law; Irrigation Plan for the Mekong Delta and SEDP guideline in 3 MKD provinces

This showcase proved that tools, like climate risk assessments, can help infrastructure investors and planners to find out where best to spend adaptation funding and find both, critical components in a single infrastructure as well as highly vulnerable infrastructures in national portfolio.



## **OUTLOOK FOR FUTURE**

- To pilot and demonstrate a service of climate risk assessment for infrastructure in Vietnam
- To recommend adaptation measures for managing climate risk on infrastructure projects
- To mainstream consideration of climate risk in planning process and policy framework, for future climate-informed investment decisions



Email: csi@giz.de



Find out more about what GIZ does on climate change adaptation at <a href="https://www.adaptationcommunity.net">www.adaptationcommunity.net</a>



Check out our video to learn more about CSI: <a href="https://www.youtube.com/watch?v=4sTBWQEC2TA">https://www.youtube.com/watch?v=4sTBWQEC2TA</a>

# **Contact Vietnam**



Mrs. Nguyen Thi Minh, Ngoc Advisor

Ngoc.nguyen1@giz.de in Hanoi



**Mr. Benjamin Hodick** Head of project

Benjamin.hodick@giz.de in Bonn



www.giz.de



https://twitter.com/giz\_gmbh https://twitter.com/adapt\_community



https://www.facebook.com/gizprofile/

Page 15 | 22 Jan. 2019 | CSI Project Presentation